

Declaration of Performance

In accordance with Regulation (EU) N° 305/2011;

1. Unique identification code of the product-type

Unique Identification Code	Product Name
See label	Decra Classic

2.	Type, batch or serial number allowing identification of the construction product as required pursuant to Article 11 (4)	See product label - Valid from 01.07.2013
3.	Intended use	Self-supporting metal sheet for roofing, external cladding and internal lining
4.	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5)	Icopal Limited Barton Dock Road, Manchester, M32 0YL. United Kingdom Production location ref: S0001-01-106
5.	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2)	Not relevant
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 4
7.	In case of the declaration of performance concerning a Construction product covered by a harmonised standard	Determination of the product type on the basis of Initial Type Testing (ITT), type calculation, tabulated values or descriptive documentation of the product under system AVCP 4 was carried out by the manufacturer.
8.	In case of the declaration of performance concerning a Construction product for which a European Technical Assessment has been issued	Not relevant

9. Declared Performance

Characteristic	Value or statement	Harmonised technical specification
Mechanical resistance	In conformity	EN 14782:2006
Watertightness	Pass	
Dimensional variability	$12 \times 10^{-6} K^{-1}$	
Release of regulated substances	NPD	
External fire resistance	F _{ROOF}	
Reaction to fire	Class F	
Durability	Steel : EN10169 -1 - DX52D + Z275/ZA255/AZ150 EN10346 EP5/EP15. - G300HS + AZ150 EN10346 EP5/EP15.	
	Nominal thickness : 0.42mm	
	Coating: - AY 300 (EN 10169 :2003) Granulates (nominal coating mass = 1600 g·m ⁻²) Acrylic varnish (nominal coating mass = 80 g·m ⁻²)	
NPD = No Performance Determined.		

*batten distance ≤ 400mm

Signed for and on behalf of the manufacturer by:

Neil Harrison
Position: Technical Director
Place: Manchester, UK
Date: 03 June 2014



..... (signature)